

ROBUS	R1000	R1300	R1300SB	R1217	R1317SB	R1600MB
Lengd (mm)	5685	6375	6375	6375	6375	6970
Breidd (mm)	2550	2550	2550	2550	2550	2550
Hæð (mm)	1871	1930	2050	2690	2820	2090
Innri mál palls (mm)	3970x2310x780	4670x2310x780	4670x2310x780	4670x2310x1600	4670x2310x1600	5250x2310x780
Hleðslurými (m3)	7,2	8,4	8,4	17,2	17,2	9,5
Hleðslurými m. hækkun (m3)	13,6	16	16	-	-	18
Tómaþyngd (kg)	2350	2800	3090	3350	3640	3650
Hámarkshleðsla (kg)	10000	13000	13000	12000	13000	16000
Hálarks heildarþyngd	12350	15800	16090	15350	16640	19650
Beislishleðsla (kg)	1800	2600	2600	2700	2700	3300
Fjöldi öxla	2	2	2	2	2	2
Hámarkhleðsla á öxul (kg)	5275	6600	6745	6325	6970	8175
Fjöðrun	Veltihásing 70x70, 6 bolta	Veltihásing 80x80, 8 bolta	Fjaðrandi hásing 80x80, 8 bolta	Veltihásing 80x80, 8 bolta	Fjaðrandi hásing 80x80, 8 bolta	Veltihásing 90x90, 8 bolta
Bremsur	300x90; 0, 2 eða 4 bremsur	300x90; 0, 2 eða 4 bremsur	350x90(359E) 2 eða 4 bremsur	300x90; 0, 2 eða 4 bremsur	350x90(359E) 2 eða 4 bremsur	350x90(359E) 2 eða 4 bremsur
Bremsuþrýstingur (bar)	160	160	160	160	160	160
Vökvaþrýstingur (bar)	180-200	180-200	180-200	180-200	180-200	180-201
Sturtutjakkur	NAS 4	NAT 6	NAT 6	NAS 6	NAT 6	2NAS6
Hámarkshraði (km/h)	40	40	40	40	40	40
Standard dekkjastærð	400/60-15,5	520/50-17	520/50-17	520/50-17	520/50-17	550/45-22,5
Sturtuhorn	52	52	52	52	52	52
Þykkt botnplötu (mm) Hardox	5	6	6	6	6	6
Þykkt í hliðum (mm) Hardox	5	6	6	4	4	6

ROBUS	R1600SB	R1620MB	R1620SB	R1900MB	R1900SB	R1920MB	R1920SB
Lengd (mm)	6970	6970	6970	7439	7439	7439	7439
Breidd (mm)	2550	2550	2550	2550	2550	2550	2550
Hæð (mm)	2220	2940	3050	2200	2200	3050	3050
Innri mál palls (mm)	5250x2310x780	5250x2310x1600	5250x2310x1600	5530x2310x780	5530x2310x780	5530x2310x1600	5530x2310x1600
Hleðslurými (m3)	9,5	19,4	19,4	10	10	20,4	20,4
Hleðslurými m. hækkun (m3)	18	30,3	30,3	21,5	21,5	32	32
Tómaþyngd (kg)	4300	4350	4900	4400	5050	5100	5750
Hámarkshleðsla (kg)	16000	16000	16000	19000	19000	19000	19000
Hálarks heildarþyngd	20300	20350	20900	23400	24050	24100	24750
Beislishleðsla (kg)	3500	3500	3500	3500	3500	3500	3500
Fjöldi öxla	2	2	2	2	2	2	2
Hámarkhleðsla á öxul (kg)	8400	8425	8700	9950	10275	10300	10625
Fjöðrun	Fjaðrandi hásing 100x100, 8 bolta	Veltihásing 90x90, 8 bolta	Fjaðrandi hásing 100x100, 8 bolta	Veltihásing 100x100, 10 bolta	Fjaðrandi hásing 100x100, 10 bolta	Veltihásing 100x100, 10 bolta	Fjaðrandi hásing 100x100, 10 bolta
Bremsur	406x120(412E) 4 bremsur	350x90(359E) 2 eða 4 bremsur	406x120(412E) 4 bremsur	400x80(408E) 4 bremsur	406x120(412E) 4 bremsur	400x80(408E) 4 bremsur	406x120(412E) 4 bremsur
Bremsuþrýstingur (bar)	160	160	160	160	160	160	160
Vökvaþrýstingur (bar)	180-202	180-203	180-204	180-200	180-200	180-200	180-200
Sturtutjakkur	2NAS7	2NAS8	2NAS9	2NAS6	2NAS6	2NAS6	2NAS6
Hámarkshraði (km/h)	40	40	40	40	40	40	40
Standard dekkjastærð	550/45-22,5	550/45-22,5	550/45-22,5	600/50R-22,5	600/50R-22,5	600/50R-22,5	600/50R-22,5
Sturtuhorn	52	52	52	52	52	52	52
Þykkt botnplötu (mm) Hardox	6	6	6	6	6	6	6
Þykkt í hliðum (mm) Hardox	6	4	4	6	6	4	4